

Product datasheet

Specifications



Wiser 1 Gang micro module switch

CCT5011-0001_AS

Main

Product brand	Schneider Electric
Range	Wiser
Product name	Wiser Micro module switch
Product or component type	Switch
Load type	Incandescent lamp Halogen lamp Fluorescent lamp LED lamp Motor

Complementary

Range compatibility	Wiser Wiser ZB/IP gateway
Colour tint	Dark grey Incandescent lamp: 2200 W at 230 V AC Halogen lamp: 2000 W at 230 V AC Motor: 1000 VA at 230 V AC LV halogen lamps: 1050 VA at 12 V AC (electronic transformer) LV halogen lamps: 500 VA at 12 V AC (wound transformer) LED lamp: 100 W at 230 V AC Compact fluorescent lamp: 100 W at 230 V AC
[Ue] rated operational voltage	220...240 V 50/60 Hz
Standby consumption	0.3 W
Associated fuse rating	16 A
Local signalling	Programming indication: LED (green, orange and red)
Communication network type	Radio frequency mesh conforming to IEEE 802.15.4
Connected auxiliaries	Maximum 10 auxiliary push-buttons
Cable length	50 m
Wiring configuration	With neutral
Connections - terminals	Screw terminals
Clamping connection capacity	1.5...2.5 mm ² for solid cable(s) 1.5...2.5 mm ² for solid stranded cable(s)
Mounting support	Wall box
Embedding depth	22 mm
Width	43 mm
Height	43 mm

Environment

Ambient air temperature for operation	0...35 °C
IP degree of protection	IP20
Environmental characteristic	Indoor use
Operating altitude	<= 2000 m
Standards	EN 60669-2-5 IEC 60669-2-5 CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	80.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.715 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)