

# Product datasheet

Specifications

## Wiser Window/Door Sensor

CCT591011\_AS



### Main

Range compatibility	Wiser hub
Range	Wiser
Product or component type	Window/door contact
Colour tint	White
Supply	Battery 3 V / CR2450

### Complementary

Device application	Security
Battery life	5 year(s)
Communication port protocol	Zigbee at 2.4 GHz conforming to IEEE 802.15.4
Device composition	sensor 50 mm x 33 mm x 16.3 mm magnet 50 mm x 9 mm x 9 mm
Alive signal	48/day
Magnet gap	< 18 mm on wood and plastic surface < 10 mm on metallic surface
Provided equipment	User manual Battery Adhesive tape Screws
Mounting mode	By screws Adhesive
Mounting support	Window frame Door frame
Net weight	30 g
Standards	IEC 60669-2-5 EN 60669-2-5
Product certifications	CE Zigbee 3.0 CB RCM EAC
Market segment	Residential

### Environment

IP degree of protection	IP20
Relative humidity	10...95 %

Ambient air temperature for operation	-10...50 °C
Operating altitude	<= 2000 m
Environmental characteristic	Indoor use

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	84.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.875 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>

## Recommended replacement(s)