

Product datasheet

Specifications

Wiser Water Leakage Sensor

CCT592011_AS



Main

Range compatibility	Wiser hub
Range	Wiser
Product or component type	Water leakage sensor
Colour tint	White
Sensor type	Flow sensor

Complementary

Material	Thermoplastic
[Ue] rated operational voltage	3 V
Supply	Battery: alkaline 2 x 1.5 V / LR03 AAA
Battery life	5 year(s)
Local signalling	1 orange LED blinking , function: battery needs replacing
Sound signalling	Alarm: siren 70 dB
Communication port protocol	Zigbee at 2.4 GHz conforming to IEEE 802.15.4
Depth	18.96 mm
Alive signal	144/day
Height	70.8 mm
Width	68.68 mm
Standards	EN 60669-2-5 IEC 60669-2-5
Product certifications	CE Zigbee 3.0

Environment

Ambient air temperature for operation	-10...50 °C
Relative humidity	10...95 %
IP degree of protection	IP44
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	114.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.075 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes

Recommended replacement(s)